

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number  
WO 2004/052667 A1

(51) International Patent Classification<sup>7</sup>: B60G 21/06

W.A. 6281 (AU). MUNDAY, Raymond, Andrew  
[AU/AU]; 4 Deacon Walk, Russelton, W.A. 6280 (AU).

(21) International Application Number:

PCT/AU2003/001637

(74) Agent: WATERMARK PATENT & TRADEMARK  
ATTORNEYS; 290 Burwood Road, Hawthorn, VIC 3122  
(AU).

(22) International Filing Date: 8 December 2003 (08.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002953153

6 December 2002 (06.12.2002)

AU


(71) Applicant (for all designated States except US): KI-  
NETIC PTY LIMITED [AU/AU]; 9 Clarke Street,  
Dunsborough, W.A. 6281 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO,  
CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB,  
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,  
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL,  
PT, RO, RU, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: HYDRAULIC SUSPENSION SYSTEM



(57) Abstract: A damping and stiffness system for a vehicle suspension system including at least two forward and two rearward wheel assemblies each associated with vehicle resilient support means (27-30) between a vehicle body and the wheel assemblies. The damping and stiffness system including: a wheel ram (11-14) with at least a compression chamber (45-48) between each wheel assembly and the vehicle body and a load distribution unit (76). The load distribution unit (76) includes two pairs of chambers (77-80), each chamber (77-80) being divided into front (89, 90) and back (91, 92) system chambers (which vary in volume proportionally and in opposite senses therein with piston motion) and the remaining pitch chambers (93-96) by interconnected pistons (81-84) supported therein. The compression chamber (45-48) of each wheel ram (11-14) is in fluid communication with a respective system chamber (89-92) wherein the vehicle is primarily supported by the vehicle resilient support means (27-30).

WO 2004/052667 A1

WO 2004/052667 A1



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,  
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*